



# Eclipse

**Residential Elevator**

## **OWNER'S MANUAL**

**(To Be Retained by Owner After Installation by Authorized Savaria Concord Dealer)**



©Savaria Concord Lifts Inc.  
Part # 000626 (Rev. 24-m01-2008)

## IMPORTANT

Ensure that only an authorized Savaria Concord DEALER installs, services, and maintains the Eclipse Residential Elevator. Under no circumstances is anyone other than a Dealer with Savaria Concord training and authorization to install, adjust, service or modify any mechanical or electrical device on this lift. Failure to follow this warning can result in safety systems compromises or defeat; this can result in serious injury or death. Savaria Concord Lifts Inc. accepts no liability for property damage, warranty claims or personal injury, including death, in this circumstance.

Lift and elevator passenger safety is the result of countless details in the equipment's design, manufacture, and installation. After installation, reliable operation and continual safe operation requires regular service and inspection at least twice per year, or more frequently where usage, environment, or local jurisdiction require. As the owner, you're responsible to ensure that regular service and inspections occur in a timely manner.

Refer to this manual for operating instructions, precautions, and for usage of the Eclipse Residential Elevator.

Upon completion of installation, the dealer must provide you with the following information and ensure to record it in this manual; in addition, either the dealer or yourself must keep any service and/or maintenance records in the Maintenance Record section of this manual.

## WARRANTY

Ensure your Savaria Concord Dealer provides you with a copy of the manufacturer's limited parts warranty and documentation relating to any Dealer labour warranty.

---

### FOR OWNER'S RECORDS

Customer Name: \_\_\_\_\_

Installing Dealer: \_\_\_\_\_

Dealer's Telephone Number: \_\_\_\_\_

Date Installed: \_\_\_\_\_

Serial/Job Number: \_\_\_\_\_



# **ECLIPSE RESIDENTIAL ELEVATOR OWNER'S MANUAL**

## *TABLE OF CONTENTS*

<b>1.</b>	<b>GENERAL SPECIFICATIONS</b>	<b>4</b>
<b>2.</b>	<b>STANDARD FEATURES</b>	<b>6</b>
<b>3.</b>	<b>OPTIONAL FEATURES</b>	<b>8</b>
<b>4.</b>	<b>OPERATING THE ELEVATOR FROM THE LANDING CONTROLS</b>	<b>9</b>
<b>5.</b>	<b>OPERATING THE ELEVATOR FROM THE CAB CONTROLS</b>	<b>10</b>
<b>6.</b>	<b>POWER FAILURE AND EMERGENCY LOWERING</b>	<b>11</b>
<b>7.</b>	<b>EMERGENCY LIGHT</b>	<b>11</b>
<b>8.</b>	<b>MANUAL LOWERING</b>	<b>12</b>
<b>9.</b>	<b>MAINTENANCE AND INSPECTION CHECKS</b>	<b>13</b>
<b>10.</b>	<b>MAINTENANCE RECORD</b>	<b>14</b>

# 1. GENERAL SPECIFICATIONS

<b>ECLIPSE RESIDENTIAL ELEVATOR</b>	
Load capacity	750 lbs. (340 kg), 950 lbs. (431 kg), 1000 lbs. (454 kg)
Rated speed	40 feet per minute (0.20 mps) (standard)
Power supply (circuit supplied by others)	208 volt - 230 volt, single phase, 60 Hz, 20 amps
Lighting supply (circuit supplied by others)	120 volt, 60 cycle, 15 amps
Drive system	Automatic 2HP-g geared roller chain variable frequency drive, complete with counterweight
Temperature operating range	- 10 °C to + 40 °C / 14 °F to 104 °F
Cab sizes	W36" x L48" x H80" (914 mm x 1219 mm x 2032 mm), Type 1, 2, 3, 4, 5 W36" x L54" x H80" (914 mm x 1371 mm x 2032 mm), Type 1, 2, 3, 4, 5 W36" x L60" x H80" (914 mm x 1524 mm x 2032 mm), Type 1, 2, 3, 4, 5 W40" x L54" x H80" (1067 mm x 1371 mm x 2032 mm), Type 1, 2, 3, 4, 5
Cab panel and finish	Solid melamine or MDF Panels (standard), unfinished Oak veneer panels (optional), finished recessed veneer panels (optional, solid hardwood raised panels (optional)
Maximum travel	50 feet (12.24 m) 60 feet (18.29 m) available where code permits
Control system	Relay logic controller complete with diagnostic LEDs
Levels and openings	Up to 4 stops / up to 2 cab openings
Pit depth requirement	6" (152 mm) minimum up to 96" (2845 mm), 11" (279 mm) minimum with buffer springs
Minimum overhead clearance	96" (2438 mm) for standard 80" cab, 114" (2896 mm) for 96" cab
Hall station and control panel finish	clear bronze anodized aluminum (standard) or stainless steel (optional) or brass (optional) rectangular (standard) or oval (optional) hall stations, keyless (standard) or keyed (optional)
Standard features	automatic cab on/off lighting recessed gate pocket digital display in car operating panel clear or bronze anodized aluminum cab entrance trim and handrail data plates, capacity tags proximity floor selection, stopping and two-way levelling motor access cover (locked and switched) home landing feature presentation drawings modular rail sections unfinished plywood sub-floor white ceiling with four incandescent pot lights melamine cab with six different color choices

## ECLIPSE RESIDENTIAL ELEVATOR

Safety features	<p>cab gate safety switch</p> <p>pit run/stop switch and car top run/stop switch</p> <p>emergency stoop and alarm buttons</p> <p>uninterruptible power supply (UPS)/battery backup system for lowering, automatic gate operation (if equipped), and electrical interlock operation and lighting in the event of a power failure</p> <p>upper and lower terminal limits</p> <p>final limit switch</p> <p>mechanical rail shoring blocks</p> <p>sling: factory pre assembled speedy sling c/w preset slack chain safety brake and switch.</p>
Options	<p>96" high cab</p> <p>rated speed - (50 fpm (0.250 mps) available where code permits)</p> <p>accordian car gate (choice of style)</p> <p>stainless steel trim pack</p> <p>brass trim pack</p> <p>automatic gate operator (accordian gates only)</p> <p>automatic gate swing landing door operator</p> <p>buffer springs (11" pit depth minimum)</p> <p>laminate flooring in finished Oak, Maple, or Cherry</p> <p>interlocks for doors by others (Kwiklock or EMI)</p> <p>keyed on/off control panel and hall stations</p> <p>cab interior in unfinished Oak, Birch, Cherry, or Maple veneer</p> <p>recessed cab panels in Cherry, Oak, or Maple veneer</p> <p>raised cab panels in solid Cherry, Oak, or Maple veneer</p> <p>telephone cabinet to match trim</p> <p>custom cab size</p>

## 2. STANDARD FEATURES

### 1) Cab Key Switch (Figure 1-A)

The key switch turns the cab controls ON and OFF. It limits the use of the elevator to only persons with authorization.

### 2) Cab Operating Panel Buttons (Figure 1-B)

#### Automatic Control

The Automatic Control Panel buttons facilitate the UP/DOWN movement of the cab between landings. After pressing a landing button, the cab automatically moves to the landing. The cab stops once it arrives at the landing.

### 3) Door Open Button (Figure 1-C)

The elevator door/gate closes automatically after a pre-set adjustable time of 8 seconds. Press the door open button to open the door/gate once the cab is at a landing.

### 4) Alarm Button (Figure 1-D)

Press the Alarm button to sound the alarm in case of an emergency.

### 5) Emergency Stop Button (Figure 1-E)

Press the Emergency Stop button to **Stop** the cab and activate the alarm buzzer at any time.



Figure 1 Cab Operating Panel

## 6) Handrail

A single handrail is on the Cab Operating Panel side of the cab.

## 7) Emergency Light

The cab emergency light remains ON in the event of a main power failure. The emergency light uses a Battery Back-Up system and includes an automatic recharger.

## 8) Landing Hall Call Station Controls

Hall Call Stations at all landings initiate the movement of the cab to the landing. An optional key switch limits the elevator's use to only persons with authorization.

## 9) Landing Door and/or Gate Interlock

The Landing Door/Gate lock prevents cab movement unless the door/gate is in the shut position with the lock in place. If the door/gate is not completely shut, the cab does not move.



Figure 2 Hall Call Station

## 10) Emergency Battery Operation

In the event of a building power failure, the door/gate system includes a temporary power back up system to continue the opening operation a number of times. Upon resuming normal building power, the back up system turns OFF and automatically recharges.

### 3. OPTIONAL FEATURES

#### **Automatic Door Opener**

- a) Press the Landing Hall Call button to call the elevator. The entrance door opens automatically once the elevator stops at the landing.
- b) Press the Remote Control (if equipped) to open the entrance door once the elevator stops at the landing.
- c) Push 'n' Go allows the entrance door to open automatically with a slight push to the door itself. The door timer is inoperative when this feature is active.

#### **Automatic Gate Opener**

- a) Press the Landing Hall Call button to call the elevator. The Gate opens automatically once the elevator stops at the landing and the entrance door is fully open.
- b) Manually open the entrance door. The Gate opens automatically once the entrance door is fully open.

#### **NOTE**

If the cab is equipped with a gate, the gate must be closed after exiting the cab. If the gate is left open, all controls will remain inoperable.

An "entry" and "exit" timer allows approximately nine seconds before the hall buttons become operational. This delay allows time for a person to enter/exit the cab.

#### 4. OPERATING THE ELEVATOR FROM THE LANDING CONTROLS

##### Automatic Operation

- 1) Insert the key (if equipped) into the switch on the Hall Call and turn the key to the ON position.
- 2) Press the Hall Call button once and release. The elevator automatically comes to your landing.
- 3) Turn the key (if equipped) to the OFF position and remove the key.
- 4) If required, turn the door handle and pull the door open.
- 5) If the cab includes a manual gate, slide the gate open and enter the cab.
- 6) Once inside the cab, close the gate, insert the key (if equipped) into the key switch, and turn the key to the ON position.

##### NOTE

When using the landing controls, the cab can only be moved (called) to the level from which you are calling. When using the control buttons in the cab, the cab can be moved to any level.



**WHEELCHAIR WHEELS MUST BE LOCKED AT ALL TIMES WHEN THE ELEVATOR IS MOVING**

## 5. OPERATING THE ELEVATOR FROM THE CAB CONTROLS

### Automatic Operation

- 1) Insert the key (if equipped) into the switch in the Cab Operating Panel. Turn the key to the ON position.
- 2) Press a Floor Landing button once and release. The elevator automatically travels to and stops at the Floor Landing.
- 3) Turn the key (if equipped) to the OFF position and remove the key.
- 4) Unlock the wheelchair wheels and exit the cab (if applicable).

#### NOTE

If the cab is equipped with a gate, the gate must be closed after exiting the cab. If the gate is left open, all controls will remain inoperable.

An “entry” and “exit” timer allows approximately nine seconds before the hall buttons become operational. This delay allows time for a person to enter/exit the cab.

## 6. POWER FAILURE AND EMERGENCY LOWERING

In the event of a power failure, the elevator includes a Battery Back-Up system that allows the user to lower the elevator from inside of the cab itself; this device operates on batteries and activates only if a main power supply failure occurs. The following steps describe this operational sequence:

- 1) For elevators with **automatic operation**, press any Floor Landing button below the floor where the elevator currently rests.
- 2) Upon arrival at the floor, the landing door automatically unlocks.
- 3) If the door includes an automatic gate, the gate opens.
- 4) Remove the key, open the manual gate, (if equipped) and exit the cab.

## 7. EMERGENCY LIGHT

In the event of a main power failure, the emergency cab lights automatically illuminate.

## **8. MANUAL LOWERING**

In the event of a power failure, batteries lower the cab to the next level and open the doors. Should the batteries fail, use the telephone to call for help. A technician can use the “Manual Hand Crank” to lower the elevator.

- 1) Instruct the person(s) in the elevator to remain calm and to stay well back from the door of the elevator. Ease their concern by telling them your intentions.
- 2) Turn the “Main Disconnect Switch” to the “OFF” position.
- 3) Locate the “Motor Access Door”; insert the Manual Hand Crank” onto the motor shaft, and crank the elevator to the next lowest level.
- 4) Use the “Emergency Key” to open the elevator door.
- 5) To exit the cab, open the lower landing door and assist the passenger(s).

## **9. MAINTENANCE AND INSPECTION CHECKS**

Regular maintenance keeps the Eclipse in proper operating condition. Please remember, as the owner of this elevator, you are responsible to ensure that maintenance and upkeep occurs on a consistent and regular basis. To ensure the continual proper operating condition of your unit, have a technician inspect the following items and, if necessary, service the elevator every six (6) months. The elevator may require additional inspections, depending on usage.

- 1) Tighten all rail and cab fastening bolts.
- 2) Lubricate the door hinges and adjust the door closure, if required.
- 3) Lubricate the rails with light grease, such as white lithium.
- 4) Inspect the travelling cable for wear. Replace if any cuts or damage to the jacket are evident.
- 5) Replace the batteries inside the control panel as indicated on the battery label.

To perform maintenance to the Kiklock (if equipped), call your Authorized Savaria Concord Dealer.





Eclipse  
Residential Elevator  
Owner's Manual

Part no. 000626  
©Copyright, 2008

Savaria Concord Lifts, Inc.  
107 Alfred Kuehne Blvd.  
Brampton, Ontario, L6T 4K3 Canada  
Tel: (905) 791-5555 Fax: (905) 791-2222  
Toll Free: 1-800-661-5112

